

LED COB LIGHT BULB

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			



DGL-MR16-02



DGL-GU10-02



DGL-HR16-02



DGL-PA20-02



DGL-PA30-02



DGL-PA38-02

Product Features

Aluminum body with high quality powder coating long life and good heat dissipation

LED Chip Epistar/Cree/Seoul/NXP/Samsung/Bridgelux for option.

Special designed COB led reflector make the lamp a real spotlight.

The efficiency of the reflector reach 98%.

Tempered glass cover safe to use.

Eco-friendly no mercury, no lead, be recognized as green light of 21st century.

Efficient conversion, reducing heat

Led lighting converts all energy into light without energy waste.

No fading will do to the documents and clothing.

Constant current quiet and comfortable

Two-year limited warranty.

UL Number: E468917

Application

Suitable for damp locations

Could be used in recessed cans, ceiling mounted fixtures at home, in shopping malls, hotels, ect.



Specification

Item No.	Input	Watt(W)	CCT(K)	Lumen(lm)	Beam Angle	Avg. Life (hours)	CRI	Dimmable
DGL-MR16-02	12V AC/DC	7	2700-7000	510-530	30°	30000	>80	Yes
DGL-GU10-02	85-265V AC	7	2700-7000	510-530	30°	30000	>80	Yes
DGL-HR16-02	85-265V AC	7	2700-7000	510-530	30°	30000	>80	Yes
DGL-PA20-02	85-265V AC	8	2700-7000	530-580	30°	30000	>80	Yes
DGL-PA30-02	85-265V AC	14	2700-7000	940-1000	35°	30000	>80	Yes
DGL-PA38-02	85-265V AC	22	2700-7000	1300-1400	35°	30000	>80	Yes

Packing details

Item	PCS/ CTN	Length (cm)	Width (cm)	Height cm)	NW (kg)	GW (kg)
MR16	100	52.5	27	12.5	4.8	7.5
GU10	100	56	27.5	14.5	6	9.6
HR16	100	56	27.5	14.5	6	9.6
PAR20	20	35.5	29	11.5	3.3	4.3
PAR30	15	51	30.7	14.6	6.6	8.2
PAR38	15	59	36	16.5	9.6	11.8

LED COB LIGHT BULB

