

LED BR LIGHT BULB

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			



DGL-BR20-03



DGL-BR30-03



DGL-BR40-03

Product Features

Aluminum heat sink good heat dissipation.

No UV or RF interference.

Patented heat sink and optical diffuser

30000 hours life time

LED Chip Epistar/Cree/Seoul/NXP/Samsung/Bridgelux for option.

No mercury, no ballast required easy installation.

Wide voltage and constant current design, no noise, no flickering.

Solid state, high shock & vibration resistant

Mercury free, 66%+ savings in energy consumption

UL Number: **E468917**

Applications:

Suitable for damp locations

Could be used in recessed cans, ceiling mounted fixtures at home, in shopping malls, hotels, ect.

LED BULB



1055 CLARK BLVD, BRAMPTON, ON, L6T 3W4 Canada
9057998009

Specification

Item No.	Input	Watt(W)	CCT(K)	Lumen(lm)	Beam Angle	Avg. Life (hours)	CRI	Dimmable
DGL-BR20-03	85-265V AC	8	2700-7000	480-500	110°	30000	>80	Yes
DGL-BR30-03	85-265V AC	12	2700-7000	860-900	110°	30000	>80	Yes
DGL-BR40-03	85-265V AC	18	2700-7000	1200-1250	110°	30000	>80	Yes

Packing details

Item	PCS/ CTN	Length (cm)	Width (cm)	Height cm)	NW (kg)	GW (kg)
BR20	20	34.5	28	12.5	3.5	4.6
BR30	15	50.5	31	16	7	8.6
BR40	15	67	41	19	10.2	12.3

LED BULB



1055 CLARK BLVD, BRAMPTON, ON, L6T 3W4 Canada
9057998009