



ORDER MATRIX | Example: K3023L

A	B	C	D	E	F
A	Series				
K3023L	COB Track Lighting (50W)				
B	Finish				
WH	White				
BK	Black				
SV	Silver				
SN	Satin Nickel				
C	Power Supply				
ND120	Non-Dimming 120V				
ND277	Non-Dimming 277V				
D120	0-10V Dimming 120V				
D277	0-10V Dimming 277V				
D	LED Available				
Philips	Philips				
Cree	Cree				
Epistar	Epistar				
Seoul	Seoul				
Osram	Osram				
E	Color Temperature				
27K	2700K				
30K	3000K				
40K	4000K				
50K	5000K				
60K	6000K				
F	Beam Spread				
16°	16° Spot				
24°	24° Narrow Flood				
32°	32° Flood				
50°	50° Wide Flood				

LED Light Engine:

- Color Temperature 2700K-6000K
- CRI 80+
- 3 Step MacAdam (3 SDMC)
- Passive aluminum heat sink
- 50,000 hrs average rated life

Electrical System:

- 120V/277V 50/60Hz input
- Over voltage, over current and short circuit protection: Auto recovery
- MTBF > 100,000 hours

Optics:

- 16° Spot, 24° Narrow Flood, 32° Flood, and 50° Wide Flood

Dimming:

- Track Dimming
 - (ELV) reverse phase control dimmers. 120V only.
 - Dimmable 100 – 10%
- Canopy Dimming
 - ELV Dimming 120V
 - 0-10V Dimming 120V or 277V

Compatibility:

- Track luminaire is designed for use with the following track systems:
 - Single Circuit/Single Neutral 120V
 - Two Circuit/Single Neutral 120V
 - Two Circuit / Two Neutral 120V
 - Two Circuit / Two Neutral 277V

Listing & Warranty:

- ETL Listed to US and Canadian standards for dry locations
- 5-Year Limited Warranty