



ORDER MATRIX | Example: FM3024A

A	B	C	D	E	F	G
A	Series					
FM3024A	COB Track Lighting					
B	Finish					
WH	White					
BK	Black					
SV	Silver					
SN	Satin Nickel					
B	Power Supply					
ND120	Non-Dimming 120V					
ND277	Non-Dimming 277V					
D120	0-10V Dimming 120V					
D277	0-10V Dimming 277V					
D	LED Available					
Philips	Philips					
Cree	Cree					
Epistar	Epistar					
Seoul	Seoul					
Osram	Osram					
E	Watt/ Lumen					
30	30W/ 2550LM					
32	32W/ 2720LM					
F	Color Temperature					
27K	2700K					
30K	3000K					
40K	4000K					
50K	5000K					
60K	6000K					
G	Beam Spread					
16°	16° Spot					
24°	24° Narrow Flood					
32°	32° Flood					
50°	50° Wide Flood					

LED Light Engine:

- Color Temperature 2700K-6000K
- CRI 80+
- 3 Step MacAdam (3 SDMC)
- Passive aluminum heat sink
- 50,000 hrs average rated life

Electrical System:

- 120V/277V 50/60Hz input
- Over voltage, over current and short circuit protection: Auto recovery
- MTBF > 100,000 hours

Optics:

- 16° Spot, 24° Narrow Flood, 32° Flood, and 50° Wide Flood

Dimming:

- Track Dimming
 - (ELV) reverse phase control dimmers. 120V only.
 - Dimmable 100 – 10%
- Canopy Dimming
 - ELV Dimming 120V
 - 0-10V Dimming 120V or 277V

Compatibility:

- Track luminaire is designed for use with the following track systems:
 - Single Circuit/Single Neutral 120V
 - Two Circuit/Single Neutral 120V
 - Two Circuit / Two Neutral 120V
 - Two Circuit / Two Neutral 277V

Mounting:

- Mounts to a standard 4" square or octagon junction box

Listing & Warranty:

- ETL listed to US and Canadian standards for wet locations
- 5-Year Limited Warranty