EXL009 LED Exit & Emergency Light

Catalog #	Prepared by LiteHarbor		
Project	Date		
Notes	-		



Description

- 1) Universal Single or Double Face
- 2) Energy Saving LED Lamps
- 3) Heavy Duty 20 Gauge Steel Housing
- Durable White Powder Coated Finish Other Finish Please Consult Factory
- 5)Etched, clear acrylic edge-lite face plate
- 6) Universally Surface Mounted, Recessed Mounted, Pendant Mounted All Are Available
- 8) Red or Green Letter Colors

Electrical

- 1) Dual Voltage Input 110-277VAC 60Hz
- 2) Solid-State Voltage Limited Charger
- 3) Solid-state Switching
- 4) Brownout Circuit
- 5) Low Voltage Disconnected
- 6) Overland/Short Circuit Protection
- 7) Test Switch/Power Indicator Light

Battery

- 1) Sealed Nickel Cadmium (Self-Powered exits only)
- 2) Maintenance-Free, Long Life
- 3) Full Recharge Time 24 Hours (max)
- 4)3.6V

61.5	507.6 443 \$\phi\$346 \$\phi\$	1
-229.44		181

Order Matrix

A	В	\mathbf{C}	D	\mathbf{E}	\mathbf{F}

A	Series
EXL009	Exit Sign

В	Input Voltage
	120V
277	277V
U	120-277V

C	Battery
	Battery Backup
AC	AC Only No battery

D	Letter Colour
GN	Green
RD	Red

Lamp Date



EXIT & EMERGENCY LIGHT

 AC LED: Long Life LED Lamps Provide Uniform Diffused Illumination 2.5W, AC

2) DC: LED Lamps 3W 3.6VDC

Warranty

EXIT: 2-Year

Battery: 15 Year Pro-rata

Е	Face
SF	Single
DF	Double

F	Mounting
SM	Surface Mounted
RM	Recessed Mounted
PM	Pedant Mounted

Other Special Requirements Please Confrim With Factory









