


DG5216LED FLOOD LIGHT





DESCRIPTION

- The circular is used as the main design, and the lamps as a whole exhibit mechanical elements, so as to achieve a sleek, exquisite and flexible purpose.
- 4mm tempered clear glass, light transmittance up to 95%, reduce the light loss.
- The lamp is composed of a lamp body, a front end cover and a rear end cover, both of which are installed with a screw structure, and at the same time, the installation screws are hidden, and the appearance is beautiful.
- Reasonable heat dissipation design, high density precision die casting aluminum lamp body, ensure the life of lamp.
- Adopt brand LED light source.
- Outdoor professional static outdoor plastic powder sprayed on surface, anti-UV, anti-corrosion and weather resistance is strong.
- Lighting structure, electrical safety compliance with EN60598 GB7000 standard requirements.
- Electric shock protection: Class I
- IP rating: IP66





L=Φ250mm H=164.5mm


UNIQUE MANUAL SWITCH DIMMING, COLOR TEMPERATURE CONTROL FUNCTION: 3CCT (3000K/4500K/6000K)


INTELLIGENT LIGHT CONTROL INDUCTION FUNCTION:


THROUGH THE LIGHT SENSOR INTELLIGENT SWITCH LAMP, NO NEED MANUAL SWITCH.











Website









APPLICATION:

Suitable for factories, gymnasiums, wharfs, billboards, buildings, lawn, gardening design and other lighting and decorative lighting places.

ORDERING GUIDE

Model	Input Voltage	Light Source	Power	Luminous Efficiency	Optional light	Luminous Flux
DG5216	AC100-240V	30 PCS	60W	>100lm/W	15/20/30/45/60/90/120	15000lm
DG5216A	AC100-240V	30 PCS	60W-RGB	>100lm/W	15/20/30/45/60/90/120	20000lm

OTHER PARAMETERS

Applicable Ambient Temperature	- 3050°C							
Total Harmonic Distortion	< 15%							
Working Temperature	RH10%-90%							
CRI	Ra>75-95 optional							
CCT	3000K	4500K	6000K					
IP Rating	IP 66							
Life Span	>20000h/>30000h/>50000h are optional							
Power Factor	> 0.95							
Frequency Range	50-60Hz							
Electric-shock safeguard	CIASS I							
Mounting	Seat Mounting / Wall Mounting							







