

AF6
6 inch Compact Fluorescent New Construction Non-IC Recessed Housing

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			



6 inch Compact Fluorescent New Construction Non-IC Recessed Housing

Housing



- 1) Die-formed aluminum for maximum heat dissipation and rust protection
- 2) Designed for New Construction installation
- 3) Housing can be installed in 1/2" to 1-3/8" thick ceilings.
- 4) Housing is Non-IC rated must be kept at least 3" away from insulation

Hanger Bar

- 1) Allow housing to be positioned and locked at any point within a 24" joist span.
- 2) Can be shortened for 12" joists
- 3) Can be positioned on long or short axis of the housing
- 4) Contain integral nail
- 5) Hanger fit onto T-bar spline for quick alignment

Junction Box

- 1) ETL listed for through branch wiring
- 2) 4 in-4 out J-box
- 3) Designed for straight through conduit runs
- 4) 1/2" and 3/4" romex wiring knockouts



Order Matrix

A	B	C	D
----------	----------	----------	----------

Item No.:AF6

A	Series
----------	--------

AF6	6"/ Compact Fluorescent New Construction NON-IC Housing
------------	--

B	Input Voltage
----------	---------------

120V
277V

C	Wattage
----------	---------

F18	CFL 18W
F26	CFL 26W
F32	CFL 32W

Ballast

- 1) Thermally protected
- 2) Electronic ballast provides full light output and rated lamp life
- 3) Flicker free and noise free operation and starting
- 4) End of lamp life protection is standard
- 5) Attached to junction box cover so it may be serviced from below the ceiling no tools required

D	Color Temperature
28K	2800K
35K	3500K
50K	5000K
60K	6000K

Lamp & Socket

See Trim for max. wattage and lamp

CRI>80%

PF>0.9

Color Temperature:2800K-6500K

Listing

ETL listed for damp location W/Feed through

Other Special requirement please confirm with factory

RECESSED DOWNLIGHT



1055 CLARK BLVD, BRAMPTON, ON, L6T 3W4 Canada
9057998009

6" COMPACT FLUORESCENT TRIM OPTICS



B6011

6" Full Reflector Baffle Cone Trim
Lamp: 18/26/32W TRT



B6012

6" Clear Reflector With Baffle
Lamp: 18/26/32W TRT



B6012W

6" Full Reflector Trim
Lamp: 18/26/32W TRT



B6022

6" Cone Trim With Reflector
Lamp: 18/26/32W TRT



BF6302

6" Shower Trim With Fresnel Lens
Lamp: 13/18/26W TRT
Gasket used to prevent moisture
Wet location listed




BF6402

6" Shower Trim With Albalite Lens
Lamp: 13/18/26W TRT
Gasket used to prevent moisture
Wet location listed



BF6502

6" Shower Trim With Drop Opal Lens
Lamp: 13/18/26W TRT
Gasket used to prevent moisture
Wet location listed



BF6512

6" Clear Specular Reflector With Drop Glass
Lamp: 13/18/26W TRT
Gasket used to prevent moisture
Wet location listed



BF6702

6" Shower Trim With Frosted Spot Lens
Lamp: 13/18/26W TRT
Gasket used to prevent moisture
Wet location listed



BF6800

6" Shower Trim With Sand Blasted Lens
Lamp: 13/18/26W TRT
Gasket used to prevent moisture
Wet location listed