

**K3033-4C**  
**Line Volt. Die-casting Track Head**

Catalog #		Prepared by	LiteHarbor
Project		Date	
Notes			



**ORDER MATRIX | Example:K3033-4C**

**A      B      C      D      E      F      G**

A	Series
K3023-4C	COB Track Light

B	Finish
WH	White
BK	Black
SV	Silver
SN	Satin Nickel

C	Power Supply
ND120	Non-Dimming 120V
ND277	Non-Dimming 277V
D120	0-10V Dimming 120V
D277	0-10V Dimming 277V

D	LED Available
Philips	Philips
Cree	Cree
Epistar	Epistar
Seoul	Seoul
Osram	Osram

**LED Light Engine**

Color Temperature 2700K-6000K

CRI 80+

3 Step MacAdam(3 SDMC)

Passive aluminum heat sink

50,000 hrs average rated life

**Electrical System**

120V/277 50/60Hz input

Over voltage,over current and short circuit protection:

Auto recovery

MTBF > 100,000 hours

**Optics**

16° Spot,24° Narrow Flood,32° Flood

**Dimming**

Track Dimming

— (ELV) reverse phase control dimmers.120V only.

— Dimmable 100-10%

Canopy Dimming

— ELV Dimming 120V

— 0-10V Dimming 120V or 277V



1055 CLARK BLVD, BRAMPTON, ON, L6T 3W4 Canada  
9057998009

E	Watt/Lumen
30/LAMP	30W / 2250LM Per Lamp
32/Lamp	32W / 2720LM Per Lamp

F	Color Temperature
27K	2700K
30K	3000K
40K	4000K
50K	5000K
60K	6000K

G	Beam Spread
16°	16° Spot
24°	24° Narrow Flood
32°	32° Flood
50°	50° Flood

### Compatibility

Track luminaire is designed for use with the following track systems:

- Single Circuit/Single Neutral 120V
- Two Circuit/Single Neutral 120V
- Two Circuit/Two Neutral 120V
- Two Circuit/Two Neutral 277V

### Mounting

Mounts to a standard 4" square or octagon junction box

### Listing & Warranty:

ETL Listed to US and Canadian standards for dry locations  
5-Year Limited Warranty

## OPTIONAL ACCESSORIES



K500

Global Adaptor

Finish: WH/BK



K600

Single/Two Circuit Live End

Finish: WH/BK



K601

Single /Two Circuit End Feed

Finish: WH/BK



K602

Single/Two Circuit Flexible Connector

Finish: WH/BK



K604

T-bar Attachment Clips For T-bar Drop Ceiling

Finish: WH/BK/SN



K605

Single/Two Circuit Floating Canopy

Finish: WH/BK



K606

Single/Two Circuit Live End With Box Cover

Finish: WH/BK



K607

Track End Cap

Finish: WH/BK



K608

Mini Coupling

Finish: WH/BK



K609

Single/Two Circuit T-Connector

Finish: WH/BK



K610

Single Circuit 90° Connector

Finish: WH/BK



K611

Single/Two Circuit X-Connector

Finish: WH/BK



K612

Live End With Cord&amp;Plug

Finish: WH/BK

Available in 2 wire,3 wire,4 wire



K5-3

Single Circuit/Two Circuit Track

Single circuit track is rated for 2400W  
features 12-gauge copper conductors and

a separate ground conductor.

Two circuit track includes 12-gauge copper  
conductors and features a double load  
capacity at 4800W max.Single/Two Circuit Track is available in  
white,black, and satin nickel finishes, and  
in 4,6, and 8-foot sizes, and can also be  
field cut to your preference.